


AI-L3-XGS2404

L3 Managed Gigabit Switch with 10G uplink

24-Port Gigabit RJ-45 + 4 Ports 10G SFP+

Real Layer 3 routing at the edge of the site — without the router price tag.

The AI-L3-XGS2404 is an AirLive L3 Managed Gigabit Switch with 10G uplink for small and medium business, branch, school and factory sites. It gives you 24-Port Gigabit RJ-45 + 4 Ports 10G SFP+, so access points, cameras, NVRs and servers each run at full speed instead of sharing one crowded pipe. Because it routes as well as switches, traffic between VLANs stays inside the box instead of going out to the router and back — quicker, and you can buy a smaller router. Set it up on site through the web interface, then run it — and every other AirLive device on that site — from AirLive AirCore, free.



24 ports

Copper + uplink, total

128 Gbps

Switching capacity

95.232 Mpps

Forwarding rate

Cloud

Managed by AirCore

What it does for you

Speed where it actually helps

Enough headroom for Wi-Fi 6/7 access points, NVRs, NAS boxes and file servers to run at full rate instead of queueing behind each other — and uplinks that reach the next building, not just the next rack.


It routes, so the router doesn't have to

Traffic between departments, floors and VLANs is handled inside the switch. The router is left to do the one job it should be doing — reaching the internet. Fewer bottlenecks, and a cheaper router.

You can run it from your desk

Adopt it into AirLive AirCore and the whole site appears on one map — topology, port status, alerts and one-click fixes, from a browser or the Windows app. Free with the product, and no truck roll.

Where it earns its keep




Office & enterprise
floors and departments



School & campus
classrooms and halls



Factory & warehouse
lines, cameras, sensors




Server & data room
racks, NAS, hosts

One app. Every site. No truck rolls.

AirLive AirCore — cloud and Windows, free with the product.

Plug the switch in, adopt it once, and the whole site draws itself on a map — every AirLive switch, access point, PON unit and camera in one place. Ports, VLANs, PoE, LAG, STP and LLDP on the AI-L3-XGS2404 are all set from a browser or from a native Windows app in the system tray. AutoPilot watches the site around the clock, heals a broken path on its own and sends the alarm by e-mail or SMS.



AirCore cloud — switch configuration, live port status and one-click adoption.

AI-L3-XGS2404 + AirCore — the switch gets smarter

The switch and the platform are built for each other. On its own the switch already connects, segments and protects the site. Adopted into AirCore it also becomes visible and self-managing: AirCore discovers the topology, keeps a copy of the configuration, watches every port and uplink, and AutoPilot proposes — or applies — the fix when a link drops, a loop forms or a rogue DHCP server appears.

In short: the switch supplies the intelligence inside the site, AirCore supplies the intelligence about the site. Everything the local web UI and CLI can do, AirCore can do remotely, for one site or a hundred.

CLOUD

AirCore Cloud

- Zero-touch adoption — plug in, adopt, done
- Live topology and hierarchical site view
- Switch, VLAN, PoE, LAG, STP and LLDP configuration
- AI AutoPilot self-healing with one-click fixes
- Unified alert inbox — e-mail and SMS notification
- Config backup, restore and firmware roll-out
- Free for distributors and system integrators

WINDOWS APP


AirCore Windows

- Native Windows 10 / 11 app — lives in the system tray
- Opens instantly, works without a browser tab
- Real-time dashboard and hierarchical topology
- Switch, VLAN, AP and PON config plus speed test
- Unified alert inbox with AutoPilot status
- Multi-camera live wall over WebRTC
- Free — same AirCore account, auto-updating

AI-L3-XGS2404 Specifications (1 / 2)

Specifications

Model: AI-L3-XGS2404



Hardware

Device Interface: 24 x 10/100/1000M RJ-45 Ports

4 x 10G SFP+ Ports

1 x RJ-45 Console Port

Standard

IEEE 802.3: Ethernet MAC Protocol

IEEE 802.3u: 100BASE-TX Fast Ethernet

IEEE 802.3ab: 1000BASE-T Gigabit Ethernet

IEEE 802.3z: 1000BASE-X Gigabit Ethernet (optical fiber)

IEEE 802.3az: Energy Efficient Ethernet

IEEE 802.3ad: Standard method for performing link aggregation

IEEE 802.3x: Flow control

IEEE 802.1ab: LLDP/LLDP-MED (Link Layer Discovery Protocol)

IEEE 802.1p: VLAN Tag LAN Layer QoS/CoS Protocol Traffic Prioritization (Multicast filtering function)

IEEE 802.1q: VLAN Bridge Operation

IEEE 802.1ad: QinQ

IEEE 802.1x: Client/Server Access Control and Authentication Protocol

IEEE 802.1d: STP

IEEE 802.1s: MSTP

IEEE 802.1w: RSTP

LED Indicators: Electrical port indicator, optical port indicator, power input indicator, system running indicator

Lighting Surge Protection:

Lightning protection: 6KV, Air discharge: 8KV, Surge: Common mode 6KV, Differential mode 2KV, Power supply: Common mode 6KV, Differential mode 2KV

Mechanical

Solid metal 19" 1U rack-mountable, Fan-less

Power

Power Input: AC100~240VAC

Switch Power Usage: max. 27W

Switching Performance

Bandwidth: 128Gbps

Packet Forwarding Rate: 95.232Mpps

Package Buffer: 12Mbit

MAC Address: 16K

Jumbo Frame: Up to 10K

VLANs: VLAN range 1-4094, maximum active VLAN is 4K

MTBF: 100000 hour

Software Function L3

IPv4: Support IPv4 Static Routes

IPv6: Support IPv6 Static Routes

Address Resolution Protocol (ARP): Static ARP

RIP: Support V1/V2

OSPF: Support V1/V2

AI-L3-XGS2404 Specifications (2 / 2)

Software Function L2

Port Function: Port Switch Configuration, Port Description Configuration, Port Speed Configuration, Port Duplex Configuration, Port Flow Control Configuration, Error Disabled Recovery, Fiber Module (DDM)

Link Aggregation: Support IEEE 802.3ad LACP, Static Trunk, Max 8 Group, Max 8 Ports/Group, Traffic Load Balancing

Storm Control: Support Broadcast Suppression, Unknown Multicast, Unknown Unicast

Port Mirroring: Support Port mirroring, RSPAN (remote port mirroring), Mirroring 4 sessions port-based (Many to One)

Port Isolation: Supported

Port Rate-limit: Supported

VLAN: Support Surveillance VLAN (16 OUI Mode (Auto/ Manual)), Voice VLAN (16 OUI Mode (Auto/Manual))

QinQ (IEEE 802.1ad) Basic, GARP VLAN Registration Protocol (GVRP), 4096 Static VLAN, 8 groups Protocol-based, 256 MAC-based, IEEE 802.1Q Tagged-based, Hybrid VLAN, protocol-based VLAN, MAC address-based

MAC Address: Supports Dynamic Address, Static MAC address, Filtering MAC Address, MAC address Black Hole, MAC address learning limit,

Spanning Tree: Support STP (IEEE 802.1d), RSTP (IEEE 802.1w) and MSTP (IEEE 802.1s) protocol

Support BPDU Filter, BPDU Guard, Auto Edge Port,

ERPS (Ethernet Ring Protection): Supported

LLDP: Support LLDP, LLDP MED

Multicast: Support Common - 256 Multicast Groups, - Immediate Leave, - Static/Forbidden Router Port, - Static/Forbidden Forward Port, - 128 profiles Filtering, - Throttling, IGMP Snooping, IGMP v1/v2, IGMP v3 Basic (BISS), IGMP v2/v3 Querier, MLD Snooping, MLD v1/v2, Multicast VLAN Registration (MVR) - IPv4

QoS: Support Trusted QoS, Queue Scheduling (WRR, WFQ, Strict Priority, Hybrid(WRR+SP or WFQ+SP)), Class of Service, Port-based, 802.1p, IP TOS Precedence, IP DSCP, Rate Limit Port-based (Ingress/Egress)

ACL: Support ACL Type L2/L3/L4, 512 MAC, based, 512 IPv4-based, 512 IPv6-based, Access Rules 1024

IPv6

IPv6 Host: Support Auto Configuration, Static IPv6 Address and Prefix Length, Static IPv6 Default Gateway, IPv6 Neighbor Discovery (ND), IPv6 Duplicate Address Detection, ICMPv6

IPv6 Application: Support HTTP/HTTPS, TELNET, SSH, SNMP, TFTP, Syslog, PING, DHCPv6

DHCP

DHCP: Support DHCP server, DHCP relay, BootP/DHCP client, DHCP snooping, DHCP relay option82, DHCP snooping option82, Requirements for Remote-ID (Access Switch Identifier), Requirements for Circuit-ID (Access port identifier). IP Pool, Static Binding

Security

AAA Authentication: Support 8 TACACS+, 8 RADIUS

Authentication Manager: Support IEEE 802.1X, MAC Auth, Web Auth, Guest VLAN, Port-based, Host-based

Account Manager: Support Local Authentication, 8 Multiple User Account, Multi-Level Security (Manager/Operator), Password Recovery Procedures

Management Access: Support Management VLAN, 256Management ACL

SSL: Support SSLv2, SSLv3, TLSv1

Port Security: Support 256 Dynamic Lock

CPU Defense Engine, DoS Prevention, DHCP Snooping (with Option 82), Dynamic ARP Inspection, 256 IP Source Guard, IP/MAC/Port Binding (IMPB), Dynamic VLAN Assignment

Diagnostics

Syslog (RFC3164): Support Local RAM, Local Flash, 8 Remote Server

System Diagnostics: Support CPU Utilization, Memory Utilization, Port Utilization, Technical Support Log

Port Diagnostics: Support Cable Test, Fiber Module Status

Network Diagnostics: Ping Test, Traceroute

UDLD: Supported

Management

Manager Access: Support CLI 3 sessions Console, 3 sessions Telnet (RFC854), WebUI HTTPS, SSH v1/v2

Manager IP: Support DHCP Client, DNS Client

Time Management: Support SNTP, Local

SNMP: Support V1/V2C/V3,

SNMP MIB: Support RFC1213 MIB-II, RFC1493 Bridge MIB, RFC2674 Bridge MIB Extensions, RFC1215 Generic Traps MIB, RFC2819 RMON MIB (Groups 1, 2, 3 and 9), RFC2737 Entity MIB, RFC3635 Ethernet-Like MIB, RFC2863 Interface MIB, SNMP-Community-MIB, SNMPv3-MIB

RMON: Support 32 entries / type RMON Management

Firmware Management: Support Firmware Upgrade/Backup, Dual Images, Configuration Download/Backup, Multiple Configurations

Configuration Management: Support Upload and Download (TFTP (RFC783), HTTP, UART), Save, Restart, Factory Defaults

Environment

Operating Temperature: 0°C to +45°C

Storage Temperature: -40°C to +70°C

Working Humidity: 10%~90%, non-condensing

Ordering information

Model

AI-L3-XGS2404

Product name

L3 Managed Gigabit Switch, 24-Port RJ-45, 4x 10G SFP+ Fiber ports.

Package content

Switch x 1, QIG x 1, Power cord x 1, Rack ear x 1

Package size

49.7 x 26.5 x 8.5 cm(L*W*H)

Package weight

N.W: 1.95kg; G.W: 2.55kg

Carton quantity

5 pcs / 1 carton

* Specifications are subject to change without prior notice. * All trademarks, logos and brand names are the property of their respective owners.