



# Wi-Fi 7 BE 11000Mbps Multi Giga PoE Access Point Central & Cloud Management, seamless roaming




AirCloud TOP-11GBE-2.5G-6GHz

## Wi-Fi 7 Features

### 320MHz Channels & 4K QAM


The AirLive TOP-11GBE-2.5G-6GHz Wi-Fi 7 enables significantly faster speeds by packing more data into each transmission. 320MHz channels are twice the size of previous Wi-Fi generations like Wi-Fi 6, which is somewhat like using a semi-truck to move boxes, compared to a moving van.

4K QAM (Quadrature Amplitude Modulation) enables each signal to more densely embed greater amounts of data compared to the 1K QAM with Wi-Fi 6/6E.



## MLO (Multi-Link Operation)

Supports more efficient load balancing of traffic among links, resulting in increased throughput and enhanced reliability. Normally, your wireless device picks a single channel to connect on whether it's on the 2.4 GHz, 5 GHz, or the new 6 GHz band. But if there's interference or that channel gets crowded, your connection slows down or even drops. This is where MLO comes in. Instead of limiting a wireless device to one channel, MLO allows it to use multiple channels across different bands at the same time. The result is, A stronger, faster connection that can handle network interference without any issue. MLO offers a multi-link connection function\*\* and multi-frequency concurrency\*.



## Multi Resource Units (RU) and Puncturing

The Airlive TOP-11GBE-2.5G-6GHz Supports Multi Resource Units (RU) and Puncturing. Multiple Resource Unit (MRU) is a new feature in Wi-Fi that's helps reducing multiple-user latency. By providing enhanced interference mitigation and efficiency. It achieves this by selectively puncturing overlapping portions of the spectrum, ensuring data travels only on unique frequencies. MRU reduces multiple-user latency by an additional 25% compared to OFDMA alone.

Puncturing: Before, busy channels meant bands could not be fully used. Data would only be sent through the primary channel. Now, with Puncturing, the interference can be blocked, opening more channels to use.

It ensures reliable connectivity, faster speeds, and seamless experiences for users.

### With Multi-RU and Puncturing



### Without Multi-RU and Puncturing



# Wi-Fi 7 BE 11000Mbps Multi Giga PoE Access Point Central & Cloud Management, seamless roaming



## AirCloud TOP-11GBE-2.5G-6GHz

### Advanced Management

### Flexible Operation - Central Management, Cloud Management, Stand-Alone AP

The AirLive TOP-11GBE-2.5G-6GHz can be a FIT AP or FAT AP. It can work as a standalone Access Point or as Repeater for home or small WLAN applications. For Large Enterprises or organizations, the TOP-11GBE-2.5G-6GHz is supported by the AirLive Wireless Controller and AirCloud with advanced and efficient central or/and cloud management.

### 24/7 365 Central and Cloud management for unlimited APs via AirCloud for Large Enterprises or Public Access

**Cloud Control:** The AirLive TOP-11GBE-2.5G-6GHz can be managed through the AirCloud once it has been added to the Cloud. This provides remote control from any location, making it advantageous for large networks of Access Points as local access is not necessary and support can be provided from a remote office. Additionally, multiple levels of control can be assigned in the Cloud, ranging from admin to viewer rights. Access Points can be easily added or removed at any time.



### Central Management via AirLive Wireless Controller for SMB


**FIT Mode:** Is a setting for the TOP-11GBE-2.5G-6GHz Access Point that allows it to be controlled by an AirLive WLAN Access Controller. The WLAN controller manages all wireless settings, encryption, and other functions, serving as the central control hub for the TOP-11GBE-2.5G-6GHz Access Point. FIT mode is ideal for SMB or large enterprise setups where multiple access points need to be controlled at once. By using FIT mode and a WLAN Access Controller, it can manage all connected APs in a single location; setup time and complexity can be greatly reduced.

### Works as standalone AP for Home or SOHO Office

**FAT Mode:** The TOP-11GBE-2.5G-6GHz Access Point functions as a standalone device with all wireless and encryption functions being controlled within the AP itself. This mode is more suitable for small setups like residential or offices with fewer APs. The FAT mode supports two operation modes: AP mode and AP Repeater, the AP works as a Universal Repeater which mean that it can repeat the wireless signal of an existing wireless network (ea. Wireless Router) over a longer distance. In AP mode, the TOP-11GBE-2.5G-6GHz can be connected to an existing network and work without the WAN port features.

### Live Status and Monitor

Monitoring your wireless internet usage by live stream graph, you can gain real-time insight into your network activity and make informed decisions about managing your internet resources.



Model	TOP-11GBE-2.5G-6GHz BE11000 Access Point
<p><b>Device Interface</b></p> <ul style="list-style-type: none"> <li>• <b>Main Chip:</b> Qualcomm IPQ5322+QCN6274+ QCA8386</li> <li>• <b>Flash:</b> NAND 128MB</li> <li>• <b>RAM:</b> 1024MB</li> <li>• <b>LAN:</b> 1 x RJ45 10/100/1000/2500Mbps</li> <li>• <b>WAN (PoE+):</b> 1x RJ-45 10/100/1000/2500Mbps</li> <li>• <b>SFP:</b> 1 x SFP+ 10G</li> <li>• <b>Wi-Fi:</b> 802.11b/g/n/ax/be (2.4GHz), 802.11a/n/ac/ax/be (5GHz) and (6GHz), Total of 6 streams, 2x2 (2.4GHz) + 2x2 (5GHz) + 2x2 (6GHz)</li> <li>• <b>Button:</b> Reset x 1</li> <li>• <b>Power Input:</b> 1 x DC 12V-3A or 1 x PoE++ 802.3bt</li> <li>• <b>Power Usages Max:</b> ≤ 36W</li> <li>• <b>Antenna:</b> Internal Wireless Antenna 2x 2.4G@1.7dBi, 2x 5G@4Bi, 2x 6GHz@4dBi</li> <li>• <b>Antenna Angle:</b> 4 antennas with a front angle &gt;130°</li> <li>• <b>LED:</b> WAN: Green, LAN: Green, Wi-Fi: Red, Green and Blue; SFP: Green, SYS: Red and Green</li> </ul> <p><b>Wi-Fi</b></p> <ul style="list-style-type: none"> <li>• <b>Standard:</b> IEEE 802.11a/b/g/n/ac/ax/be 20/40/80/160/240/320 MHz channels</li> <li>• <b>Functions:</b> Multi-SSID 12 (4 per radio), SSID hidden, SSID isolation, Support 5G Prior for a faster Ethernet, Band Steering, RF power adjustable, Wi-Fi time on/off to save energy</li> <li>• <b>Security:</b> OPEN, WPA/WPA2PSK-TKIPAES, WPA3-SAE, EAP 802.1x (EAP only for 2.4 and 5GHz).</li> <li>• <b>Modulation:</b> OFDMA, 4096QAM, MLO</li> <li>• <b>Seamless Roaming:</b> 802.11k, 802.11v</li> <li>• <b>Wi-Fi Advanced:</b> Wireless client isolation to improve the wireless stability</li> <li>• <b>Wireless Channel</b></li> <li>• 2.4G: 1~13 (CE Channel) (region dependent)</li> <li>• 5.8G: 36~48, 36~64, 100~140, 149~165 (region dependent), 6G: 1, 5, 9, 13, 17, 21, 25, 29, 33, 37, 41, 45, 49, 53, 57, 61, 65, 69, 73, 77, 81, 85, 89, 93, 97, 101, 105, 109, 113, 117, 121, 125, 129, 133, 137, 141, 145, 149, 153, 157, 161, 165, 169, 173, 177, 181, 185, 189, 193, 197, 201, 205, 209, 213, 217, 221, 225, 229, 233 (region dependent)</li> <li>• <b>Wireless Frequency:</b> 2.4GHz: 2.4GHz ~ 2.484GHz, 5GHz: 5.150GHz~5.850GHz, 6GHz: 5.925GHz ~ 7.125GHz (region dependent)</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Wireless Speed:</b> 11000Mbps: 2.4GHz: 688Mbps, 5GHz: 4323Mbps, 6GHz: 5764Mbps</li> <li>• <b>Wireless TX Power:</b> 2.4G: ≤24±2dBm, 5.8G: ≤21±2dBm, 6G: ≤20±2dBm (region dependent)</li> <li>• <b>2.4G EVM:</b> 802.11b: ≤-10dB; 802.11g: ≤-25 dB; 802.11n: ≤-28dB; 802.11ax: ≤-35dB; 802.11be: ≤-38 dB</li> <li>• <b>5G EVM:</b> 802.11a: ≤-25dB; 802.11n: ≤-28dB; 802.11ac: ≤-32dB; 802.11ax: ≤-35dB, 802.11be: ≤-38 dB</li> <li>• <b>6G EVM:</b> 802.11a: ≤-25dB; 802.11n: ≤-28dB; 802.11ac: ≤-32dB; 802.11ax: ≤-35dB, 802.11be: ≤-38 dB</li> <li>• <b>ppm:</b> ±20ppm</li> <li>• <b>Wireless seamless roaming technology</b> A combination of technologies, including Fast BSS Transition (FT), 802.11k and 802.11v. These technologies work together to allow devices to quickly and seamlessly switch between access points without interrupting the connection or requiring the user to manually reconnect. <b>802.11k</b> provides better signal information for device decisions on which access point to connect to. <b>802.11v</b> offers QoS information for device selection of the best access point based on its needs.</li> </ul> <p><b>LAN</b></p> <ul style="list-style-type: none"> <li>• <b>LAN (IPv4):</b> Static IP, Get IP from AC, Get IP from Gateway</li> <li>• <b>LAN (IPv6):</b> Set IPv6 Address, IPv6 DNS</li> </ul> <p><b>Security</b></p> <ul style="list-style-type: none"> <li>• <b>Filter Rule:</b> MAC Filter</li> <li>• <b>MAC filtering:</b> MAC ACL.</li> </ul> <p><b>VLAN</b></p> <ul style="list-style-type: none"> <li>• VLAN support SSID Max 4 per Band</li> </ul> <p><b>Cloud</b></p> <ul style="list-style-type: none"> <li>• AirCloud access support in AP Mode</li> </ul> <p><b>FIT/FAT Operation Mode</b></p> <ul style="list-style-type: none"> <li>• FIT Mode: AP works with AC Controller (Enterprise)</li> <li>• FAT Mode: AP works standalone (Home use)</li> </ul> <p><b>Management</b></p> <ul style="list-style-type: none"> <li>• Web-UI, Remote Management, SNMP V1/V2/V3, WLAN Controller, Cloud Management System AirCloud</li> </ul> <p><b>Max Concurrent users</b></p> <ul style="list-style-type: none"> <li>• 192 (Support user quantity limited, Max 64 users to access each band)</li> </ul>

\* Specification will be changed without prior notice

\* All trademarks, logos and brand names are the property of their respective owners.



Model	TOP-11GBE-2.5G-6GHz BE11000 Access Point
<p><b>AP/AP Repeater Mode</b></p> <ul style="list-style-type: none"><li>• <b>AP:</b> In this mode, the AP Wireless and Cable Interface are bridging together. Without NAT, Firewall and all network related functions.</li><li>• <b>AP Repeater:</b> In this mode the AP works as a Universal Repeater which can repeat the wireless signal of other wireless devices like a Wireless Router or Access Point. All interfaces are bridged together. Without NAT, Firewall, and all network related functions.</li></ul> <p><b>Data Statistics</b></p> <ul style="list-style-type: none"><li>• AP Down Stream, AP Up Stream</li><li>• Wi-Fi Analyzer (2.4, 5, 6GHz)</li><li>• Device Info</li></ul> <p><b>Multiple Language</b> English</p> <p><b>ESD/Surge Protection</b></p> <ul style="list-style-type: none"><li>• <b>ESD:</b> Air Discharge: ±8KV, Contact Discharge: ±6KV</li><li>• <b>Electrical Surge:</b> Common Mode: 2KV, Differential Mode: 1KV</li></ul> <p><b>Environment</b></p> <ul style="list-style-type: none"><li>• <b>Operating temperature:</b> -10°C ~ +55°C</li><li>• <b>Storage Temperature:</b> -40°C ~ +70°C</li><li>• <b>Storage Humidity:</b> 5% ~ 95% (non-condensing)</li><li>• <b>Enclosure:</b> Aluminum bottom, ABS Top.</li></ul> <p><b>Standard package</b></p> <ul style="list-style-type: none"><li>• <b>Product size:</b> 20.8 x 20.8 x 4.60 cm(L*W*H)</li><li>• <b>Package size:</b> 25.5 x 24.8 x 7.5 cm(L*W*H)</li><li>• <b>Package Weight:</b> N.W: 0.9555kg; G.W: 1.268kg</li><li>• <b>Package content:</b> 1x TOP-11GBE-2.5G-6GHz, 1x Ceiling mount, 1x QIG</li></ul> <p><b>Standard carton package</b></p> <ul style="list-style-type: none"><li>• <b>Quantity:</b> 16 pcs / 1 carton</li><li>• <b>Dimensions</b> 53.5 x 32.8 x 51.5cm (L*W*H)</li><li>• <b>Weight</b> 20.30kg (G.W)</li></ul> <p><b>Ordering information</b></p> <ul style="list-style-type: none"><li>• <b>AirLive AirCloud TOP-11GBE-2.5G-6GHz</b> 11be 11000Mbps Multi Giga PoE Access Point, Central and Cloud management supported</li></ul>	

\* Specification will be changed without prior notice

\* All trademarks, logos and brand names are the property of their respective owners.

