

Wi-Fi 6 AX 3000Mbps Gigabit PoE Access Point

Central & Cloud Management, seamless roaming

AirCloud TOP-30AX-1G

airlive®




Wi-Fi 6 AX3000	Central Management Supported	Cloud Management supported	Live Status Monitor	AP/Gateway Mode
MediaTek Chipset	1G WAN Port	Seamless Roaming	FIT/FAT Mode	48V PoE

Overview

TOP-30AX-1G service 24/7 365 Management via the AirCloud

The Airlive TOP-30AX-1G is an advanced Wi-Fi 6 compliant 3000Mbps Dual Band multi functions Access Point which features 1x 1Gbps LAN port and 1x 1Gbps WAN 48V PoE input port. It is supported by AirCloud and AirLive Wireless controller. Large Enterprises or organizations can centrally manage large numbers of APs in a single location with the Wireless controller. Or do the management and access from anywhere anytime with an internet connection via AirCloud, cloud-based platform. Moreover, it can work as a standalone AP at home or office when setting in FAT operation mode.



Wireless Seamless Roaming

Additionally, the TOP-30AX-1G supports Wireless Seamless Roaming technology 802.11k/802.11v and Fast BSS Transition (FT) that users can stay connected and productive while on the move. These technologies work together to allow devices to quickly and seamlessly switch between access points without interrupting the connection or requiring the user to manually reconnect. This technology is particularly useful in environments where users need to move around, such as in large offices, airports, shopping malls, and campuses.



Features

- Wi-Fi 6 11a/b/g/n/ac/ax compliant
- OFDMA, MU-MIMO
- 2T2R 3000Mbps Wireless High Speed (574Mbps + 2402Mbps)
- 20/40/80/160Mhz Channel
- Concurrent dual bands 2.4Ghz and 5Ghz
- Seamless Roaming
- 1 x 10/100/1000Mbps WAN RJ-45 PoE Port
- 1 x 10/100/1000Mbps LAN RJ-45 Port
- 802.3af/at PoE power input (WAN)
- FIT/FAT Operation mode
- AP and AP Gateway Operation Mode
- Cloud Management Support via AirCloud
- AirLive Wireless Controller Supported
- Up to 8 Multiple SSID
- VLAN Support in AP Mode
- QoS in AP Gateway Mode
- URL/MAC/IP Filtering
- Wi-Fi Timer
- Up to 128 Users

Wi-Fi 6 AX 3000Mbps Gigabit PoE Access Point

Central & Cloud Management, seamless roaming



AirCloud TOP-30AX-1G


Advanced Management

Flexible Operation - Central Management, Cloud Management, Stand-Alone AP

The AirLive TOP-30AX-1G can be a FIT AP or FAT AP. It can work as a standalone Access Point or Gateway for home or small WLAN applications. For Large Enterprises or organizations, the TOP-30AX-1G is supported by the AirLive Wireless Controller and AirCloud with advanced and efficient central or/and cloud management.

24/7 365 Central and Cloud management for unlimited APs via AirCloud for Large Enterprises or Public Access

Cloud Control: the AirLive TOP-30AX-1G can be managed through the AirCloud once it has been added to the Cloud. This provides remote control from any location, making it advantageous for large networks of Access Points as local access is not necessary and support can be provided from a remote office. Additionally, multiple levels of control can be assigned in the Cloud, ranging from admin to viewer rights. Access Points can be easily added or removed at any time.



Central Management via AirLive Wireless Controller for SMB


Fit mode is a setting for the TOP-30AX-1G Access Point that allows it to be controlled by an AirLive WLAN Access Controller. The WLAN controller manages all wireless settings, encryption, and other functions, serving as the central control hub for the TOP-30AX-1G Access Point. Fit mode is ideal for SMB or large enterprise setups where multiple access points need to be controlled at once. By using Fit mode and a WLAN Access Controller, it can manage all connected APs in a single location; setup time and complexity can be greatly reduced.

Works as standalone AP for Home or SOHO Office

Fat mode: The TOP-30AX-1G Access Point functions as a standalone device with all wireless and encryption functions being controlled within the AP itself. This mode is more suitable for small setups like residential or offices with fewer APs. The Fat mode supports two operation modes: AP mode and AP Gateway mode. In AP Gateway mode, the TOP-30AX-1G works as a gateway and uses its WAN port connecting to a modem/router via PPPoE, DHCP, or Static IP. In AP mode, the TOP-30AX-1G can be connected to an existing network and work without the WAN port features.

Live Status and Monitor

Monitoring your wireless internet usage by live stream graph, you can gain real-time insight into your network activity and make informed decisions about managing your internet resources.



Model	TOP-30AX-1G AX3000 Access Point
Device Interface Main Chip: MediaTek MT7981B+MT7976CN+MT7531AE Flash: SPI NOR 16MB RAM: 256MB DDR3 Ethernet (LAN): 1 x RJ45 10/100/1000Mbps WAN (PoE): 1x RJ-45 10/100/1000Mbps Wi-Fi: 802.11b/g/n/ax 2T2R(2.4Ghz), 802.11a/n/ac/ax 3T3R (5Ghz) Button: Reset x 1 Power Input: 1 x DC 12V/1.5A or 1 x 48V PoE 802.3af Power Usages Max: ≤ 15W Antenna: Internal Wireless Antenna 2 x 2.4Ghz, Gain: 4.6dBi, 2 x 5Ghz, Gain: 4dBi WAN WAN: PPPoE, DHCP, Static IP, (Bridge (AP Mode)) Wi-Fi Standard: IEEE 802.11a/b/g/n/ac/ax, 20/40/80/160 MHz channels Functions: Multi-SSID 8 (4 per radio), Support SSID hidden, Support seamless roaming, Support client isolation, Support 5G Prior for a faster Ethernet., RF power adjustable, Support MAC filter, Wi-Fi time on/off to save energy, Support user quantity limited, Max 64 users to access each band. Security: Open, WPA, WPA2PSK_TKIPAES, WPA2_EAP, WPA3 Modulation : OFDMA, 1024QAM Seamless Roaming : 802.11k, 802.11v Wi-Fi Advanced: Wireless client isolation Wireless Channel 2.4G: 1~13 (CE Channel) (region dependent) 5.8G: 36~48, 36~64, 100~140, 149~165 (region dependent) Wireless Frequency: 2.4Ghz: 2.4GHz ~ 2.484GHz, 5GHz: 5.150GHz~5.850GHz (region dependent) Wireless Speed: 3000Mbps Wireless High Speed (574Mbps + 2402Mbps) Wireless TX Power: 2.4G: ≤23±2dbm, 5.8G: ≤23±2dbm (region dependent) 2.4G EVM: 802.11b: ≤-10dB; 802.11g: ≤-25 dB; 802.11n: ≤-28dB; 802.11ax: ≤-35dB 5G EVM: 802.11a: ≤-25dB; 802.11n: ≤-28dB; 802.11ac: ≤-32dB; 802.11ax: ≤-35dB ppm: ±20ppm	Wireless seamless roaming technology A combination of technologies, including Fast BSS Transition (FT), 802.11k and 802.11v. These technologies work together to allow devices to quickly and seamlessly switch between access points without interrupting the connection or requiring the user to manually reconnect. 802.11k provides better signal information for device decisions on which access point to connect to. 802.11v offers QoS information for device selection of the best access point based on its needs. Security Filter Rule: URL Filter/Mac Filter/IP Filter URL/MAC/IP filtering: White list/Black List. DMZ: DMZ Port Forwarding Rule/Range: TCP/UDP VLAN VLAN support SSID Max 4 per Band Support hardware watchdog function: Automatic recovery of abnormal equipment, and maintenance free. Cloud - AirCloud Access support in Gateway/AP Mode FIT/FAT Operation Mode FIT Mode: AP works with AC Controller (Enterprise) FAT Mode: AP works standalone (Home use) Management - Web-UI, Remote Management, WLAN Controller, Cloud Management System AirCloud Max Concurrent users: 128 Parental Control (Gateway Mode) - Mac Address Filtering, URL Filtering, IP Filtering

* Specification will be changed without prior notice

* All trademarks, logos and brand names are the property of their respective owners.



Specification

Model	TOP-30AX-1G AX3000 Access Point
AP/AP Gateway/AP Repeater Mode AP: In this mode, the AP Wireless and Cable Interface are bridging together. Without NAT, Firewall and all network related functions. AP Gateway: In this mode, the WAN page is enabled and PPPoE, DHCP or Static IP can be selected. NAT is enabled and PC's in LAN ports share the IP to ISP through WAN port. VPN Pass Through (Gateway Mode) - IPsec, PPTP, L2TP Data Statistics - WAN Down Stream, WAN UP Stream - Wi-Fi Analyzer (2.4 and 5Ghz) Multiple Language - English LED Indicator - Triple color (Sys-Red, 2.4G-Green, 5.8G-Blue) ESD/Surge Protection - Air: ±8KV, Contact: ±4KV - Common Mode: 2KV, Differential Mode: 1KV Environment Operating temperature: -20°C ~ +45°C Storage Temperature: -40°C ~ +70°C Storage Humidity: 5% ~ 95% (non-condensing) Standard package Product size: 18.6 x 18.6 x 3.70 cm(L*W*H) Package size: 24.5 x 23.5 x 7.6 cm(L*W*H) Package Weight: N.W: 0.520kg; G.W: 0.7645kg Package content: 1x TOP-30AX-1G, 1x Ceiling mount, 1x QIG Standard carton package Quantity: 20 pcs / 1 carton Dimensions 50.6 x 41.0 x 49.1cm (L*W*H) Weight 16.60kg (G.W) Ordering information AirLive AirCloud TOP-30AX-1G 11ax 3000Mbps Gigabit PoE Access Point, Central and Cloud management supported	

* Specification will be changed without prior notice

* All trademarks, logos and brand names are the property of their respective owners.

AirLive