

2.5Gbps Base-T Multi Gigabit Switch, plug and play

6-Port Multi Giga incl 4 x 2.5G RJ45, 2 x SFP+ 10G

Live-2TX402

airlive®



4-port
100/1000M/2.5G

Multi-Gigabit
Auto-negotiation

Cat.5e cable
suitable

2x 10G SFP+
Uplink


ESD
protection

Plug and Play

Overview

Painless Upgrading your Network Connection to 2.5Gbps & SFP+ 10G Super High speed

The AirLive Multi-Giga switch, Live-2TX402, supports 4 RJ45 and 2 SFP+ ports for delivering up to 2.5Gbps extra high-speed connection on RJ-45 and 10G SFP+ on fiber optic. With the 2.5G multi-Giga switch, you can connect to a variety of 2.5GbE-enabled devices, such as NAS | NVR | PC | Server | Laptop, for enjoying faster experience and handle bandwidth-hungry applications. Designed in a slim sized solid housing, it's an affordable, space-saving solution suitable to Home and SMB network applications.



Multi Gigabit for Interconnect

With the AirLive Live-2TX402 2.5Gbps switch, it is possible to connect several high-speed devices together via RJ-45 connections using a normal Cat.5e network cable. Higher bandwidth improves the playback quality of 4K/8K videos, prevents lag for Gaming, smooths speed when download or upload large data, increases data transfer speed when doing backup to a NAS drive. Use the 10G SFP+ as uplink to a larger network with higher speed.

Features and Specifications

- AirLive Live-2TX402 2.5Gbps Switch with SFP+ 10G
- 4 x 10/100/1000/2500Mbps RJ45
 - 2x 10G SFP+
 - All ports at Multi Gigabit high speed, auto-negotiation
 - Providing satisfied bandwidth for various network devices, such as online gaming, multi-media, NAS, Server system
 - Super Fast 2.5Gbps RJ-45 and 10Gbps SFP+ Networking
 - Existing Cat5e cable suitable, painless upgrading
 - Plug and Play, Zero configuration
 - Compact size for Home or SMB Network Connectivity



2.5 Times Faster

2.5GbE is 2.5 times faster than standard Ethernet (1GbE), upgrade network performance to boost productivity.



Video Streaming

Higher bandwidth improves the playback quality of 4K/8K videos.

Works with existing cables


No special cables or connectors are required to take advantage of 2.5GbE. Simply use your existing CAT5e cables as normal with your new 2.5GbE infrastructure.



Gaming

No lag when you are Gaming.

Model	AirLive Live-2TX402
<p>Hardware</p> <ul style="list-style-type: none"> • Device Interface: 4 x 10/100/1000/2500 RJ45 2x 1.25G/2.5/10G SFP + 6-port totally • Standard IEEE802.3u 100Base-TX IEEE802.3ab Gigabit 1000Base-T IEEE802.3bz 2.5GBase-T IEEE 802.3z 1000BASE-X Gigabit Ethernet (optical fiber) IEEE 802.3ae 10G Ethernet (optical fiber) IEEE802.3x Flow Control and Back Pressure • Industry standard compliant EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD), IEN61000-4-5 (Surge) • LED Indicators: PWR (power supply), Link/Act (Indicator), 2.5G (Indicator). • Lightning Surge / ESD Protection: Support Port Surge Protection: Common Mode 4KV, Differential Mode 2KV (Class C); ESD air 8KV, Contact 6KV (Class C). • Mechanical Solid Metal Housing, Desktop <p>Power</p> <ul style="list-style-type: none"> • Power Input: 12V/1A Power Adapter <p>Switch Architecture Performance</p> <ul style="list-style-type: none"> • Switching architecture: Store and Forward Switch Capacity: Back-plan up to 60Gbps Packet Forwarding Rate; 44.64Mpps Packet Cache: 8Mbit MAC Address: 4K Transfer mode: Store and Forward MTBF:100000 hour 	<ul style="list-style-type: none"> • Transmission Distance 10Base-T: Cat3,4,5 UTP(≤250 meter) 100Base-TX: Cat5 or later UTP(150 meter) 1000Base-TX: Cat5e or later UTP(150 meter) 2500Base-TX: Cat5e or later UTP(150 meter) • Fiber Medium: 1000BASE-SX: 62.5μm MMF (multi mode) (Minimum range: 2m~275m) or 50μm MMF 1000BASE-LX: 62.5μm/50μm MMF (Minimum range: 2m~550m)or 10μm SMF (Minimum range: 2m~5km) 2500BASE-X: G.652D SMF (Single mode) (Minimum range: 2m~500m or 2m~5Km) 10GBASE-SR: OM1/OM2/OM3 or above MMF (Operating range: 2m~300m) 10GBASE-LR: IEC B1.1 and B1.3 SMF (Minimum range: 2m~10km) <p>Environment</p> <ul style="list-style-type: none"> • Operating Temperature: 0°C to +40°C • Storage Temperature: -40°C to +70°C • Working Humidity: 10%~90%, non-condensing • Storage Humidity: 5%~95%, non-condensing <p>Standard package of switch</p> <ul style="list-style-type: none"> • Product size: 14.0 x 9.3 x 2.8 cm(L*W*H) • Package size: 20.3 x 16.0 x 5.5 cm(L*W*H) • Package Weight: N.W: 0.33Kgs; G.W: 0.46Kgs • Package content: 1 x Switch, 1 x Power Adapter <p>Standard carton package</p> <ul style="list-style-type: none"> • Quantity: 40 pcs / 1 carton • Dimensions 58.0 x 33.5 x 44.5cm (L*W*H) • Weight 19.5Kgs (G.W) <p>Ordering Information</p> <ul style="list-style-type: none"> • Model: Live-2TX402 • Name: 6-port 2.5Gbps Multi Gigabit Switch, incl. 4 x 2.5G RJ45 and 2x SFP+ 10G, Plug and Play, Auto-Negotiation • Related product AirLive USB-25G USB3.1/3.0 to 2.5Gbps Base-T adapter



Built for High-Speed connectivity

* Specification will be changed without prior notice

* All trademarks, logos and brand names are the property of their respective owners.