AirLive NVR Email Setup using Gmail

Note: This example was made using the AirLive ANVR WebUI, setting up the Email direct in the ANVR is also possible when a monitor and mouse are connected to the ANVR. The Email setup is the same as when using the WebUI.

When you use Gmail to send an alarm, you must turn on 2-Step Verification in Gmail and use the new application specific password (created in the Gmail account) in the NVR settings. When using your normal Gmail password, the login will not work, and the NVR will not send any alarm messages.

		Ē	Live View		Playb	ack	٠	Set	up	2	s Sr	nart					
Client	*		Email														
System	*																
Camera	~		Server Authen	tication	0 On	Off											
Hard Disk	~		Username		Examp	le@gma	il.com										
Alarm	~		Password			•											
Alant			SMTP Server		smtp.g	mail.con	n										
Alert	~		SMTP Port		465				TLS/SS	L							
Network	*		Snapshot Inter	val	2s			۷C	Attach	Image							
ICP/IP																	
PPPOE			Sender		Examp	le											
DDNS			Sender's Addre	ess	Examp	le@gma	il.com										
Port																	
Port Mapping			Select Recipier	nt	Recipie	ent1		•									
Email			Recipient		Examp	le1											
Multicast			Recipient Add	ress	Examp	le1@gm	ail.com		Tes		2						
FTP			Arming Sched	iule													
User	*		Edit														
Maintenance	~		0	2	4	6	8	10	12	14	16	18	20	22	24		
			Mon												1	1 Arming	
			Wed												3	3	
			Thu												4	4	
			Fri												5	5	
			Sat												e	6 Unarmed	
			Sun												7	7	
			Holiday	2	4	6	8	10	12	14	16	18	20	22	24	8	
				2	-1	~	Ŭ		.2		.0	.0	20	22	24		
			Save	1													

After you enter your information press the "Save" button to Save the settings. To Test the settings, press the "Test" button. When the settings are correct you will receive a test email on your specified account.

When you did not receive an email, make sure you entered the correct email and password.

If Port 465 is blocked, please use Port 587.